


MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 0251-2310167 /2310212

Fax : 0251-2310192

Email : rokalyan@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Sidhivinayak Sankul,
3rd floor, Near Oak Baug,
Station Road,

Kalyan - 421301

RED/S.S.I

Consent No: MPCB/16/ 16 / 1701001301

Date: 19/01/2017

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2016

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

.....
CONSENT is hereby granted to

M/s. Leeladhar Chemicals,
Vill-Kamba, Post-Varap,
Tal-Kalyan, Dist-Thane.

Located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW (M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: - 31/12/2020.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Purification of OTD& PTS amide Amide mixture and products		
	I) OTS Amide (Pure)	3	T/M
	II) PTS Amide (95%)	3	T/M
	No spent acid shall be generated		

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 0.8M³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 0.4M³.
- (iii) **Trade Effluent Treatment:** The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

No.	Parameter	Limit	Unit
1	pH	Between	5.5 to 9.0
2	Suspended Solids	Not to exceed	100 mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	100 mg/l.
4	COD	Not to exceed	250 mg/l.
5	Oil & Grease	Not to exceed	10 mg/l.
6	Total Dissolved Solids	Not to exceed	2100 mg/l.
7	Sulphates	Not to exceed	1000 mg/l.
8	Chlorides	Not to exceed	600 mg/l.

- (iv) **Trade Effluent Disposal:** The treated effluent shall be recycled to maximum extend back in the process and remaining shall be send to Common ETP with your sister concern M/s.A,S.Chemopharma Pvt Ltd. Both the industries will be jointly responsible for operating the ETP and achieving the standards. There shall be no discharge of effluent outside industry premises.

