


MAHARASHTRA POLLUTION CONTROL BOARD

Phone :	0240-2473461		Paryavaran Bhavan, A - 4/1, MIDC Area, Chikalthana, Near Seth Nandlal Dhoot Hospital, Jalna Road, Aurangabad - 431210
Fax :	0240-2473462		
Email :	roaurangabad@mpcb.gov.in		
Visit At :	http://mpcb.gov.in		

Green/SSI

Date: 24/01/2017

SRO-Aurangabad/Consent/1701001876

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Asha Mahila Bachat Gat,
Plot No. H-5/48, MIDC Chikalthana,
Aurangabad.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31/05/2018.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity
1	Sukdi	42 T/M
(By only Physical Mixing without use of chemical & reaction process)		

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall be Nil.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 0.30 M³

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

- (iv) Trade Effluent Disposal: The treated effluent shall be used on land for Gardening.

1) pH	Between	5.5 to 9.0
2) Suspended Solids	Not to exceed	100 mg/l.
3) B.O.D. 3 days 27 °C	Not to exceed	100 mg/l.
4) C.O.D.	Not to exceed	250 mg/l.
5) Oil & Grease	Not to exceed	10 mg/l.
6) T.D.S.	Not to exceed	2100 mg/l.

