

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 020-25811627

Fax : 020-25811029

Email : sropune1@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Jog Center, 3rd floor, Mumbai Pune Road,  
Wakdedwadi,

Pune - 411003

**Green/S.S.I**

**Date: 15.03.2017**

**Consent No: SRO/PUNE-II/CONSENT/1703000775**

**Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008**

**[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].**

CONSENT is hereby granted to

**M/s. Nirmitee Construction,  
Sr. No. 2/1,3,4, 5/1 to 4, 6/1to 2, 7/1 to 3,  
8/2 to 3, 10/1/A, 10/2 to 3, 11/A/2/2,  
11/A/1/2/D Bavdhan (Bk),  
Tal-Mulshi, Dist-Pune**

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to: 29.02.2020**
- 2. The Consent is valid for the manufacture of -**

Sr. No.	Product Name	Maximum Quantity	UOM
1	Ready Mix Concrete	1945.0	M <sup>3</sup> /M

### 3. CONDITIONS UNDER WATER (Prevention & Control of Pollution) ACT, 1974:

- The daily quantity of trade effluent from the factory shall not exceed Nil M<sup>3</sup>
- The daily quantity of sewage effluent from the factory shall not exceed 2.05 M<sup>3</sup>
- Trade Effluent : Nil**
- Trade Effluent Disposal: N.A.**
- Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

- |                       |               |     |       |
|-----------------------|---------------|-----|-------|
| (1) Suspended Solids  | Not to exceed | 100 | mg/l. |
| (2) BOD 3 days 27o C. | Not to exceed | 100 | mg/l. |

- Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

6. Daily cleaning/removal of dust accumulation inside the plant shall be carry out with industrial vacuum cleaner
7. Two level tyre washing facility shall be provided at entry and exit points for transit mixture vehicle

**(iii) Raw Material Storage:**

1. Storage silos of cement & fly ash shall be equipped with adequate capacity of dust collection system such as multi-cyclone followed by bag house assembly.
2. Handling of Cement, Sand, fly ash and aggregates shall be carried out with mechanical closed system only.
3. Manual operations shall be permitted only in closed shed, equipped with dust control system at the loading point as well as roof top secondary dust control system
4. All conveyor belt of sand, aggregates shall be covered with tin sheets and at transfer points dust collection system to be installed to avoid secondary fugitive emissions.
5. Mixing section of cement, aggregate & sand shall be equipped with adequate capacity dust collection system such as multi cyclone followed by bag house so as to limit dust emissions.
6. Storage area of sand & aggregates shall be equipped with roof top water sprinkler system.
7. The production plant interlocked with air pollution control system
8. Alternative power supply system should cover both the production & air pollution control system.

**B) Control Equipment:**

- 1). Industry shall provide dust collector of sufficient capacity to control the emissions.
- 2) You shall provide wind breaking walls.
- 3) You shall develop a green belt along the periphery of unit.
- 4) You shall construct metalled roads within premises.
- 5) You shall follow regular cleaning & wetting of the ground within premises.
- 6) All the cementations material shall be stored in silos.

**C). Ambient air quality at a distance of 10 mtrs from source OR the plant Boundary. Whichever is nearer, shall meet the following standards:**

(i) PM10	Not to exceed	100 microgram/m <sup>3</sup>
(ii) PM2.5	Not to exceed	60 microgram/m <sup>3</sup> ,

**6. Conditions for D.G. Set**

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

- b. Industry shall obtain registration from CPCB as a re-refiner of Used oil having environmentally sound technology as per the provisions of Hazardous Waste (Management & Handling) Rules 1989 & Amendment Rules 2003 before commencement of production.
- c. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- d. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

**9. Industry shall comply with following additional conditions:**

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes /

(vii) The authority shall provide water treatment & disposal facility for generating effluent from their activity. They shall comply with provisions under the Water (Prevention & Control of Pollution) Act, 1974.

(viii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
---------	---------------	----------	-----	-----------	----------

--N.A.--

(viii) Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

- |   |                |          |
|---|----------------|----------|
| (i) Domestic purpose  | ...            | 3.5 CMD  |
| (ii) Water gets Polluted & Pollutants are Biodegradable             | ... For Mixing | 6.5 CMD  |
| (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic | ...            | 0.00 CMD |
| (iv) Industrial Cooling, spraying in mine pits or boiler feed       | ...            | 0.00 CMD |

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
- (ii) The authority shall provide adequate Air Pollution Control arrangement at the source. They shall comply with provisions under the Air (Prevention & Control of Pollution) Act, 1981 & conditions prescribed in following A, B & C.
- (iii) Solid waste from transit mixer washing, muck generated from RMC shall either re-use through recovery unit/re-calming system or disposed off at designated approved site by local body for debris/construction waste.

A) Pollution Control Measures:

(i) In-house measures:

1. All material points should be covered
2. Barricading all around the periphery of the plot boundary of height minimum 20 feet or 5 feet above free fall air emission area, whichever is higher with tin sheets. Same may be extend above with netion clothing whichever required.
3. Water sprinkling/chemical dust stabilizing agent spraying system along the periphery inside the premises of RMC
4. Tree Plantation along the periphery inside boundary of the RMC.
5. Internal work area shall be cement concreted/Asphalted

- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

#### 7. Standards for Stack Emissions:

The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	LDO	8.0	Kg/Hr

- (i) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	D.G. Set 82.5 KVA	3.0

- (ii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iii) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (vi) Other Conditions:
  - 1) The industry should not cause any nuisance in surrounding area.
  - 2) The industry should monitor ambient air quality regularly.

#### 8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

- (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
			--N.A.--	

- (ii) Treatment: - NIL
  1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
  2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.
- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such

- sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- xiii. Industry shall voluntarily stop the manufacturing activity, if complaints arises against the noise/air/water pollution.
- xiv. Operation of RMC plant shall be in day time only. The day time is reckoned in between 6 am to 6 pm.
- xv. The Consent should not be construed as exemption from obtaining necessary NOC from any other Government agencies as may deem fit necessary.
- xvi. This consent is issued as per Office Order No.E-17/2008,dtd.18.02.2011 /07.03.2008 and as per power delegation to S. R.O.'s for grant Consent upto Capital investment 50 Corers (Green Category).
- xiv. The Board reserves the right to add/amend/revoke any condition in this consent and same shall be binding on the applicant.
10. The Capital investment of the industry is Rs. 60.35 Lakhs.

For AND ON BEHALF OF M.P.C.BOARD,



(D.P.Koparkar)  
Sub Regional Officer  
M.P.C.Board,Pune-II

To,  
M/s. Nirmitee Construction,  
Sr. No. 2/1,3,4, 5/1 to 4, 6/1to 2, 7/1 to 3,  
8/2 to 3, 10/1/A, 10/2 to 3, 11/A/2/2,  
11/A/1/2/D Bavdhan (Bk),  
Tal-Mulshi, Dist-Pune

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	5000.0	0195511	27.02.2017	ICICI Bank
2	5000.0	0195512	27.02.2017	ICICI Bank

*Received*  
*[Signature]*