

# MAHARASHTRA POLLUTION CONTROL BOARD

|  |   |  |
|--|---|--|
| Tel: 24010437/24020781/24014701                              |  | Kalpataru Point, 2 <sup>nd</sup> - 4 <sup>th</sup> Fl. |
| Fax: 24024068 / 24023516                                     |   | Opp. Cine Planet Cinema.                               |
| Website: <a href="http://mpcb.gov.in">http://mpcb.gov.in</a> |   | Near Sion Circle, Sion (E)                             |
| E-mail: <a href="mailto:mpcb@vsnl.net">mpcb@vsnl.net</a>     |   | Mumbai-400 022.  |

Red/S.S.I

Date: 01/09/2012

Consent No: BO/JD (APC)/EIC No. PN-152322-12/O- 399

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Lustrous Industries,  
Plot No. A-26, MIDC Chakan,  
Tal. Khed, Dist. Pune

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. ~~The Consent to Operate is granted for a period up to 28/02/2016.~~
2. The Consent is valid for the manufacture of -


| Sr. No. | Product Name   | Maximum Quantity | UOM  |
|---------|----------------|------------------|------|
| 1       | Silver Plating | 2400             | m2/M |
| 2       | Copper Plating | 800              | m2/M |
| 3       | Tin Plating    | 400              | m2/M |

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 6.0 M<sup>3</sup>.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 1.5 M<sup>3</sup>.

#### (iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:



*[Handwritten signature]*

| Sr.no | Parameter                                     | Limits  |
|-------|---|---|
| 1     | pH  | Between 5.5 to 9.0  |
| 2     | Temperature                                   | Should not exceed 5 c above the ambient temperature of the receiving body |
| 3     | BOD 3 days 27 Deg. C                          | Not to exceed 30 mg/l   |
| 4     | COD   | Not to exceed 250 mg/l  |
| 5     | Oil & Grease                                  | Not to exceed 10 mg/l   |
| 6     | Suspended Solids                              | Not to exceed 100 mg/l.   |
| 7     | Cyanide (as 'CN')                             | Not to exceed 0.2 mg/l.   |
| 8     | Ammonical nitrogen (as N)                     | Not to exceed 50 mg/l.  |
| 9     | Total residual chlorine (as Cl <sub>2</sub> ) | Not to exceed 1.0 mg/l.   |
| 10    | Cadmium (as Cd)                               | Not to exceed 2.0 mg/l.   |
| 11    | Nickel (as Ni)                                | Not to exceed 3.0 mg/l  |
| 12    | Zinc (as Zn)                                  | Not to exceed 5.0 mg/l  |
| 13    | Chromium as Cr Hexavalent Total               | Not to exceed 0.1 mg/l.   |
| 14    | Copper (as Cu)                                | Not to exceed 3.0 mg/l.   |
| 15    | Lead (as Pb)                                  | Not to exceed 0.1 mg/l.   |
| 16    | Iron (as Fe)                                  | Not to exceed 3.0 mg/l.   |
| 17    | Total metal                                   | Not to exceed 10.0 mg/l.  |

(iv) **Trade Effluent Disposal:** The metal bearing industrial effluent shall be segregated and reused back into process and remaining treated effluent shall use on land for gardening. There shall not be any discharge outside the factory premises.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

- |                       |               |           |
|-----------------------|---------------|-----------|
| (1) Suspended Solids  | Not to exceed | 100 mg/l. |
| (2) BOD 3 days 27o C. | Not to exceed | 100 mg/l. |

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

| Sr. No. | Type Of Waste | Quantity | UOM | Treatment | Disposal |
|---------|---------------|----------|-----|-----------|----------|
|---------|---------------|----------|-----|-----------|----------|

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

- |                              |     |         |
|------------------------------|-----|---------|
| (i) Domestic                 | ... | 2.0 CMD |
| (ii) Industrial Processing   | ... | 6.0 CMD |
| (iii) Industrial Cooling     | ... | 0.0 CMD |
| (iv) Agriculture / Gardening | ... | 1.0 CMD |



*[Handwritten Signature]*

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

**5. CONDITIONS UNDER AIR ACT :**

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

**a. Control Equipment:**

- i. Wet Scrubber of sufficient capacity shall be operated properly and continuously
- ii. There shall not be any secondary (fugitive) emission.

**6. Conditions for D.G. Set :N.A.**

**b. Standards for Emissions of Air Pollutants:**

|       |                 |               |                        |
|-------|-----------------|---------------|------------------------|
| (i)   | SPM/TPM         | Not to exceed | 150 mg/Nm <sup>3</sup> |
| (ii)  | So <sub>2</sub> | Not to exceed | kg/day                 |
| (iii) | Acid Mist       | Not to exceed | 35 mg/Nm <sup>3</sup>  |

(i) The applicant shall observe the following fuel pattern:

| Sr. No. | Type Of Fuel | Quantity | UOM |
|---------|--------------|----------|-----|
|---------|--------------|----------|-----|

The applicant shall erect the chimney(s) of the following specifications:-

| Sr. No. | Chimney Attached To | Height in Mtrs. |
|---------|---------------------|-----------------|
|---------|---------------------|-----------------|

|   |          |                                |
|---|----------|--------------------------------|
| 1 | Scrubber | 2.5 above roof top of building |
|---|----------|--------------------------------|

The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

(ii) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

**(vi) Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly

**7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:**

(i) The Industry shall handle hazardous wastes as specified below.

| Sr. No. | Type Of Waste                                   | Quantity | UOM  | Disposal            |
|---------|---|----------|------|---------------------|
| 1       | 34.3 Chemical sludge from waste water treatment | 5.0      | KG/D | CHWT/SDF Ranjangaon |

(ii) Treatment: - NIL

- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.



2. The industry should comply with the under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008.
- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008.
- d. Industry shall comply with following additional conditions:
- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

