

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 0253-2365150

Fax : 0253-2365140

Email : ronashik@mpcb.gov.in

Visit At : <http://ronashik@mpcb.gov.in>



Udyog Bhavan, First Floor Trimbak Road,

Near ITI, Satpur

Nashik - 422007

RONashik / Amendment/ 1901 00 1334

Date : 18/1/19

**Sub: AMENDMENT IN CONSENT**

**M/s. Glenmark Pharmaceuticals Ltd.,  
Plot No.E-37, 37/1,38 and 39,MIDC Satpur,  
Tal. & Dist. Nashik**

- Ref:-**
1. Consent to Operate granted by Board on 03.10.2016.
  2. Application of the industry vide UAN No.0000059574.
  3. Reply submitted by the industry vide letter dtd.09.01.2019 & 11.01.2019.

Consequent upon Consent to Operate granted by the Maharashtra Pollution Control Board to **M/s. Glenmark Pharmaceuticals Ltd., Plot No.E-37, 37/1,38 and 39,MIDC Satpur, Tal. & Dist. Nashik** under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974, under, Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Hazardous Wastes (Management & Handling and Trans boundary Movement) Rules, 2016 vide above reference cited at 1, application submitted by the industry vide above reference cited at 2 and request of the industry for considering the said application for amendment in the consent to operate vide above reference cited at 3.

In view of above, Consent to Operate granted vide no. MPCB/RONK/SRN/CR-198/2278/2016(1610000077) dtd.03.10.2016 having validity up to **31.08.2020** to the said industry is hereby amended as follows:

**The Condition No. 5 of the said Consent shall be read as -**

**5. CONDITIONS UNDER AIR ACT :**

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

**Control Equipment:**

Industry shall provide dust collector/ scrubber of sufficient capacity to control the emissions from processing section as well as boiler and same shall be operated continuously and effectively so as to avoid any sort of air pollution and smell nuisance problems in the surrounding area.

**a. Standards for Emissions of Air Pollutants:**

(i)	SPM/TPM	Not to exceed	150	mg/Nm <sup>3</sup>
(ii)	SO <sub>2</sub>	Not to exceed	180	Kg/Day
(iii)	Acid mist	Not to exceed	035	mg/Nm <sup>3</sup>

**b. The applicant shall observe the following fuel pattern:-**

Sr. No.	Type Of Fuel	Quantity	UOM
1.	HSD	3.6	KL/D.
2.	LDO	3	KL/D.
3.	Bio fuel	3	KL/D.



c. The applicant shall erect the chimney (s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtr.
1	Boiler 1 & 2	15 each
2	Boiler(850 Kg/hr- Standby )	15
3	DG Set ( 750 KVA)	5mtr. above roof level.
4.	DG Set ( 250 KVA)	3mtr above roof level.
5.	DG Set ( 1250 KVA)	30.

- d. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- e. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- f. **Other Conditions:**
- The industry should not cause any nuisance in surrounding area.
  - The industry should monitor stack emissions and ambient air quality regularly.
- g. **Conditions for D.G. Set:**
- Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
  - Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
  - The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m. and night time is reckoned between 10 p.m to 6 a.m.
  - Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
  - Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
  - A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use. D.G. Set shall be operated only in case of power failure.
  - The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

*(Signature)*  
18/1/15



The Condition No. 12 of the said Consent shall be read as –

12. The Capital investment of the industry as on 30.06.2018 is Rs.90.24 Cr as per CA certificate submitted by the industry.

All other conditions of the Consent to Operate shall be remain unchanged.

(P. M. Joshi)  
Regional Officer, Nashik

To,  
M/s. Glenmark Pharmaceuticals Ltd.,  
Plot No.E-37, 37/1, 38 and 39,MIDC Satpur,  
Tal. & Dist. Nashik.



Copy to:-  
Sub-Regional Officer, MPCB, Nashik.

Received Consent fee of -

Amount in Rs.	Transition /DR.No.	Date
75000/-	7616334	01.11.2018.
75000/-	7619023	11.01.2019.