v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated to the following standards.

Suspended Solids

Not to exceed

B.O.D. 3 days 27 ⁰C

-do-

100 mg/l

Sewage Effluent Disposal:-Treated domestic effluent shall be soaked in a vi) soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for plantation only.

Non- Hazardous Solid Wastes :vii)

Type of Waste

Treatment Quantity

Disposal

..... N. A.

Other conditions :- 1) The authorities shall strictly comply Rules and Regulations of Forest Department. 2) The industry shall take effective steps for tree plantation of important indigenous variety of trees to ameliorate pollution of industry depending upon topographical / geographical features of area.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose

 $0.50~\mathrm{CMD}$

(ii) Water gets Polluted &

Pollutants are Biodegradable

0.00 CMD

(iii) Water gets Polluted, Pollutants

are not Biodegradable & Toxic ...

0.00 CMD

(iv) Industrial Cooling, spraying

in mine pits or boiler feed

0.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Quantity

a. Control Equipment:

Dust collection system of sufficient capacity shall be provided to saw mill to bring air pollutants within prescribed norms.

6. Standards for Stack Emissions:

SPM/TPM i)

Not to exceed 150 mg/NM³

ii) SO₂ Not to exceed

The applicant shall observe the Milow

ing fual pattern:-

Type Of Fuel

UOM

ulloluly