

MAHARASHATRA POLLUTION CONTROL BOARD

Sub-Regional Office, Thane-II

Phone : 022-25802272 /25829582
Fax : 022-25805398
Email : srothane2@mpcb.gov.in
Visit At : <http://mpcb.gov.in>



5th Floor, Office Complex Bldg.,
Near Mulund Check Naka,
Wagale Estate,
Thane-400 604

No. MPCB/SROT-II/B- 1906000002

Date: 3 /06/2019

Sub : Amendment in the consent to operate M/s. India Leather Company, Gala No. 1,2,3,4,5,6 & 7- Gr. Floor, Gala No. 101, 102, First Floor, Gala No. 201, 202, Kala House, Aarti industrial Estate, Waliv Road, Gokhivare, Vasai (E), Tal- Vasai, Dist- Paighar.

Ref : 1) Consent granted by Board vide no. MPCB/SRO-Thane-II/CONSENT/O/ 1811000681, Dated 15/11/2018 valid up to 30/04/2022
2) Your Application No. MPCB-CONSENT_AMMENDMENT-0000003011

Consent to Operate granted under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974; under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Hazardous & Other Wastes (M & TM) Rules, 2016 to M/s. India Leather Company, Gala No. 1,2,3,4,5,6 & 7- Gr. Floor, Gala No. 101, 102, First Floor, Gala No. 201, 202, Kala House, Aarti industrial Estate, Waliv Road, Gokhivare, Vasai (E), Tal- Vasai, Dist- Palghar, vide above reference No.1 is hereby amended as under:

1. 6. Standards for Stack Emissions:

Conditions for D.G. Set :-

- Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- D.G. Set shall be operated only in case of power failure.
- The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Diesel	15	Ltr/Hr

(ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	DG Set (60 KVA)	7.0 above the roof

(All other conditions of the consent shall be remain unchanged.)



For & on behalf of
Maharashtra Pollution Control Board

(Signature)
(V. V. Killedar)
Sub Regional Officer, Thane-II

To,
M/s. India Leather Company,
Gala No. 1,2,3,4,5,6 & 7- Gr. Floor,
Gala No. 101, 102, First Floor, Gala No. 201, 202,
Kala House, Aarti industrial Estate, Waliv Road,
Gokhivare, Vasai (E), Tal- Vasai, Dist- Palghar.

Copy to: - Regional Officer, MPCB, Thane