# MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010706/24010437

Fax: 24023516

Website: http://mpcb.gov.in Email: cac-cell@mpcb.gov.in



Kalpataru Point, 2nd, 3rd and 4th floor, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

Circle, Sion (E), Mumbai-400022

**RED/L.S.I (R58)** 

No:- Format1.0/CC/UAN No.MPCB-

CONSENT AMMENDMENT-0000012955/CO/2407000055

To, M/s. Sequent Scientific Ltd. B-32, G-2 & G-3,MIDC Mahad Mahad,Raigad-Raigad



Date: 20/07/2024

Sub: Grant of Amendment for Amendment in Consent to Operate under Change in Product Mix.

Ref:

- 1. Amendment in Consent to Operate under Change in Product Mix. accorded vide No. Format1.0/CC/UAN No.0000163814/CO/2307001500, dated 24/07/2023, which is valid upto 30/09/2027.
- 2. Environmental Clearance accorded vide no. SIA/MH/IND2/167228/2020 Dated 11/07/2022
- 3. Minutes of 2nd Meeting of Technical Committee (2023-2024) for clarification about No Increase in Pollution Load held on 09/06/2023.
- 4. Minutes of 4th Consent Committee meeting of 2024-2025 held on 14/06/2024.

Your application No.MPCB-CONSENT AMMENDMENT-0000012955 Dated 16.02.2024

For: grant of Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 6 and Rule 18(7) of the Hazardous & Other Wastes (Management & Transboundary Movement) Rules 2016 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- 1. The consent to operate is granted for a period up to 30/09/2027
- 2. The capital investment of the project is Rs.83.1613 Crs. (As per C.A Certificate submitted by industry )
- 3. Consent is valid for the manufacture of:

Sr No	Product	Maximum Quantity	иом					
Prod	Products							
1	Albendazole	68	MT/M					
2	S-Methoprene	0.5	MT/M					
3	Carprofen OR Oxfendazole OR Fenbendaole OR Ricobendazole	7	MT/M					
4	Diclazuril Intermediate OR Nitroscanate	2	MT/M					

Sr No	Product	Maximum Quantity	иом
5	Tetramisole OR DMZ API	4	MT/M
6	Clorsulon Intermediate	3	MT/M
7	FTC	15	MT/M
8	Nitroxynil OR Afoxolaner OR Levomisole HCL OR Fluazuron OR Lufenuron	3	MT/M
9	Buparvaquone OR Fluralaner OR Flubendazole	2	MT/M
10	Sarolaner OR Toldimafos Sodium	4	MT/M
11	Triclabendazole OR Butaphosphane	7	MT/M
12	R & D New Development Product	1.5	MT/M
13	Solvent Distillation for Recovery	75	KL/D

# 4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr No	Description	Permitted (in CMD)	Standards to	Disposal Path	
1.	Trade effluent 87.53		As per Schedule -I Partly recycle 69. CMD & partly CET CMD		
2.	Domestic effluent	13.6	As per Schedule - I	I Recycle 100% to achieve ZLD	

# 5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr No.	Stack No.	Description of stack/ source	Number of Stack	Standards to be achieved
1	S -1	Boiler (3 TPH)	1	As per Schedule -II
2	S -1	Boiler (3 TPH Standby)	1	As per Schedule -II
3	S -2	Thermopack (4 Lac Kcal/Hr)	1	As per Schedule -II
4	S -3	Thermopack (2 Lac Kcal/Hr)	1	As per Schedule -II
5	S -4	Reactor 102, Tray Drier	1	As per Schedule -II
6	S -5	Reactor 201	1	As per Schedule -II
7	S -6	Reactor 202	1	As per Schedule -II
8	S -7	Standby to Process Reactors	1	As per Schedule -II
9	S -8	HCl Storage Tank	1	As per Schedule -II
10	S -9	DG Set- (500 KVA)	1	As per Schedule -II
11	S -10	DG Set- (500 KVA)	1	As per Schedule -II
12	S -11	Diesel Engine Fire pump	1	As per Schedule -II
13	S -12	Warehouse chemical dispensing	1	As per Schedule -II
14	S -13	DC-1 P-III-Micronisation	1	As per Schedule -II
15	S -14	DC-2 P-III-Micronisation	1	As per Schedule -II

Sr No.	Stack No.	Description of stack / source	Number of Stack	Standards to be achieved
16	S -15	DC-3 P-II-Sifter/Multimill	1	As per Schedule -II
17	S -16	DC-4 P-III-Micronisation	1	As per Schedule -II
18	S -17	DC-5-AHU Filter cleaning room	1	As per Schedule -II
19	S -18	DC-6-Behind warehouse (Micronisation)	1	As per Schedule -II
20	S -19	DC-7 P-III Multi Mill	1	As per Schedule -II
21	1 S -20 DC-8 P-III(Sifter Operation)		1	As per Schedule -II
22	22 S -21 Fume hood-QC lab		1	As per Schedule -II
23	3 S -22 Fume hood-PDL lab		1	As per Schedule -II

#### 6. Non-Hazardous Wastes:

Sr No	Type of Waste	Quantity	UoM	Treatment	Disposal
1	Boiler Ash	600	MT/A	Sale	Sale to Brick Manufacturer
2	General Scrap (empty containers, glass waste, wood waste & metal waste)	80	MT/A	Sale	Sale to authorized party
3	Contaminated Glassware	200	Kg/M	Sale	Sale to authorized party

# 7. Conditions under Hazardous & Other Wastes (M & T M) Rules 2016 for Collection, Segregation, Storage, Transportation, Treatment and Disposal of hazardous waste:

Sr No	Category No./ Type	Quantity	UoM	Treatment	Disposal
1	36.2 Spent carbon or filter medium	1.8	MT/A	HW for Co-Processing shall be routed through authorized pre-processing /Recycle*	HW for Co-Processing shall be routed through authorized pre- processing/Sale to authorized party/CHWTSDF
2	20.3 Distillation residues	419.88	MT/A	HW for Co-Processing shall be routed through authorized pre- processing/Incineration	HW for Co-Processing shall be routed through authorized pre- processing/CHWTSDF
3	28.6 Spent organic solvents	1106.64	MT/A	HW for Co-Processing shall be routed through authorized pre- processing/*Recycle	HW for Co-Processing shall be routed through authorized pre- processing/Sale to authorized party/CHWTSDF

Sr No	Category No./ Type	Quantity	UoM	Treatment	Disposal
4	35.1 Exhaust Air or Gas cleaning residue	50	MT/A	Landfill	CHWTSDF
5	26.3 Spent acid	513.6	MT/A	Recycle*	Sale to authorised party / CHWTSDF
6	28.1 Process Residue and wastes	8.1 Process esidue and astes  HW for Co-Processing shall be routed throug authorized preprocessing/Sale to authorized		processing/Sale to	HW for Co-Processing shall be routed through authorized pre- processing/CHWTSDF
7	28.3 Spent carbon	18	MT/A	HW for Co-Processing shall be routed through authorized pre- processing/Recycle*	HW for Co-Processing shall be routed through authorized pre- processing/Sale to authorized party/CHWTSDF
8	35.3 Chemical sludge from waste water treatment	128	MT/A	Landfill महाराष्ट्र	CHWTSDF
9	5.1 Used or spent oil	0.5	MT/A	HW for Co-Processing shall be routed through authorized pre- processing/Recycle*	HW for Co-Processing shall be routed through authorized pre- processing/Sale to authorized party/CHWTSDF
10	37.3 Concentration or evaporation residues	on 1085.76 MT/A		Recycle*	Sale to authorised party / CHWTSDF

<sup>\*</sup> Industry shall ensure disposal to the Actual user having permissions under Rule 9 of Hazardous and other Waste (M & TM) Rules, 2016

#### 8. Conditions under Batteries (Management & Handling) Rules, 2001:

Sr No	Type of Waste	Quantity	UoM	Disposal Path
1	Battery Waste	1.50	MT/A	Sale to Authorized Recycler

#### **Specific Conditions for used Batteries:**

The applicant shall ensure that used batteries are not disposed of in any manner i. other than by depositing with the authorized dealer/ manufacturer/ registered recycler/ importer/ re-conditioner or at the designated collection center.

- ii. The applicant shall file half-yearly return in Form VIII to the M.P.C. Board.
- Bulk consumers to their user units may auction used batteries to registered recyclers only.

# 9. Conditions under Plastic Waste Management Rules, 2016 (Notification dtd. 18/03/2016):

Sr No	Type of Waste	Quantity	UoM	Disposal Path
1	Plastic waste	3.00	MT/M	Sale to Authorized Recycler

# 10. Conditions under E-Waste Management:

I	Sr No	Type of Waste	Quantity	UoM	Disposal Path
	1	E-Waste	1.00	MT/A	Sale to Authorized Recycler

#### 11. Treatment and Disposal of Biomedical Waste generated to CBMWTSDF:

Sr.No	Category	Type of Waste	Quantity not to exceed (Kg/M)	Segregation Color coding	Treatment & Disposal
1	Yellow	a) Human Anatomical waste	500.00	Yellow colored non- chlorinated plastic bags	CBMWTSDF
2	Red	Contaminated waste (Recyclable)	0.50	Red colored non chlorinated plastic bags or containers	CBMWTSDF
3	White (Translucent)	Waste sharps including Metals	0.50	Puncture proof, Leak proof, tamper proof container	CBMWTSDF
4	Blue	a) Glassware	10.00	Puncture proof & leak proof boxes or containers with blue colored marking.	CBMWTSDF

- 12. The Board reserves the right to review, amend, suspend, revoke this consent and the same shall be binding on the industry.
- 13. This consent should not be construed as exemption from obtaining necessary NOC/ permission from any other Government authorities.
- 14. The Project Proponent shall also comply with the Industry specific standards notified under Environmental Protection Act, 1986.
- 15. This consent is issued with overriding effect on earlier Amendment in Consent to Operate under Change in Product Mix. accorded vide No. Format1.0/CC/UAN No.0000163814/CO/2307001500, dated 24/07/2023, which is valid upto 30/09/2027...
- 16. This consent is issued pursuant to the decision of the 4th Consent Committee Meeting of 2024-25 held on 14/06/2024.
- 17. The industry shall obtain necessary permission from the Directorate of Industrial Safety and Health (DISH).
- 18. The applicant shall comply with the conditions of the Environmental Clearance granted vide letter No. SIA/MH/IND2/167228/2020 Dated 11/07/2022.
- 19. The applicant shall not carry out any excess production or produce new products without Consent of the Board and without Environmental Clearance wherever it applicable.

- 20. The applicant shall properly collect, transport & regularly dispose-off the Hazardous Waste to CHWTSDF, in compliance of the Hazardous and other Waste (M & TH) Rule-2016 an keep proper manifest thereof.
- 21. Industry shall comply with direction issued to CETP on 22.01.2021, regarding installation of two-way SCADA, Auto-sampler, Non-Return Valve (NRV) with positive discharge to CETP chamber.
- 22. This consent is issued pursuant to the decision of Minutes of the 2nd Meeting of Technical Committee (2023-24) for change in product mix Dated. 09/06/2023. This Consent is issued based on self-assessment of Pollution Load submitted by you in Board's prescribed format and Certificate of "No Increase in pollution load" issued by empaneled auditors M/s. Sadekar Enviro Engineers Pvt. Ltd. vide letter dtd. 13/03/2023. If any violation and / or submission of misleading information are noticed, then the consent issued will stand automatically cancelled and you have to follow the procedure of EIA Notification, 2006 and Amendments thereof for obtaining Environmental Clearance.
- 23. The industry shall ensure connectivity of continuous online monitoring system to the Board server & data to be transmitted directly from Data Logger to the Board server.
- 24. Industry shall comply with all the conditions stipulated in Environmental Clearance and ensure display/upload of six- monthly compliance monitoring report on their official website.
- 25. Industry should not manufacture any other product for which permission is not granted by the Board
- 26. Industry shall ensure connectivity of OCEMS to Board server.
- 27. Guidelines for Pre-processing & Co-Processing of Hazardous & Other Wastes in cement plant as per H & O (M & TM) Rules, 2016 prepared by Central Pollution Control Board shall be strictly followed.
- 28. Industry shall strictly follow the provisions of Hazardous & Other Wastes (Management & Transboundary Movement) Rules, 2016.
- 29. The applicant shall make an application for renewal of consent 60 days prior to date of expiry of the consent.

This consent is issued on the basis of information/documents submitted by the Applicant/Project Proponent, if it has been observed that the information submitted by the Applicant/Project Proponent is false, misleading or fraudulent, the Board reserves its right to revoke the consent & further legal action will be initiated against the Applicant/Project Proponent.

# **Received Consent fee of -**

Sr.No	Amount(Rs.)	Transaction/DR.No.	Date	Transaction Type
1	625000.00	TXN2303000560	05/03/2023	Online Payment

# Copy to:

- 1. Regional Officer, MPCB, Raigad and Sub-Regional Officer, MPCB, Mahad
- They are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Sion, Mumbai



#### **SCHEDULE-I**

#### **Terms & conditions for compliance of Water Pollution Control:**

- 1. A] As per your application, you have segregated trade effluent into weak stream & strong stream and provided Effluent Treatment Plant (ETP) comprising of:
  - i) Strong COD/TDS stream of 71.32 CMD Treatment system comprising of Primary (Collection tank, Neutralization tank, Equalization tank, Flash mixer, Primary Clarifier/Primary Settling Tank) ., Stripper, Reverse osmosis, Multi effect evaporator, ATFD followed by Sludge treatment.
  - **ii) Weak COD/TDS stream of 16.21 CMD -** Treatment system comprising of Primary (Collection tank, Neutralization tank, Equalization tank, Flash mixer, Primary Clarifier/Primary Settling Tank), Secondary (Activated sludge process), Tertiary (Pressure sand filter, Activated carbon filter).
  - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent:

Sr.No	Parameters	Limiting concentration not to exceed in mg/l, except for pH			
(1)	рН	6.0 -8.5			
(2)	BOD (3 days 27°C)	30			
(3)	COD	250			
(4)	TSS	महाराष्ट्र 100			
(5)	Oil & Grease	10			
(6)	Total Dissolved Solids	2100			
(7)	Sulphate	1000			
(8)	Chlorides	600			
(9)	% Sodium	60%			
(10)	Iron	5			
(11)	Zinc	5			

- C] The treated effluent 69.03 CMD along with domestic sewage 13.6 CMD shall be recycled/reused into the process, cooling tower and remaining 18.5 CMD shall be discharged into CETP for further treatment & disposal after confirming above standards. In no case, effluent shall find its way outside factory premises.
- D] The Industry shall ensure connectivity online monitoring system to the MPCB server including separate energy meter for pollution control system.
- 2. A] As per your application, primary treated sewage connected to Effluent Treatment Plant for further treatment & disposal.
  - B] Industry shall comply prescribed standards & disposal path as prescribed at Sr. No. 1 B & C of schedule I.

- 3. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification there of & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto.
- 4. The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
- 5. The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Act, 1974 and as amended, by installing water meters and other provisions as contained in the said act:

Sr. No.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	161.00
2.	Domestic purpose	17.00
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	67.00
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	0.00
5.	Gardening —	24

6. The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance/ CREP guidelines.

# **SCHEDULE-II**

# Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC) system and erected following stack (s) to observe the following fuel pattern:

Stack No.	Source	APC System provided/proposed	Stack Height(in mtr)	Type of Fuel	Sulphur Content(in %)	Pollutant	Standard
	Boiler (3TPH)	Cyclone Separator followed by Wet Scrubber		Briquette 750 Kg/Hr	0.06	TPM	50 Mg/Nm³
S -1	Boiler (3 TPH Standby)	Cyclone Separator followed by Wet Scrubber	30.00	OR Coal (used only in case of contigency) 950 Kg/Hr	-	SO2	21.6 Kg/Day
	The same and all (4.1.)	Cyclone Separator		Delanostha		TPM	50 Mg/Nm <sup>3</sup>
S -2	Thermopack (4 Lac Kcal.Hr)	followed by Wet Scrubber	30.00	Briquette 50 Kg/Hr	0.06	SO2	1.44 Kg/Day
	Thermopack (2 Lac	Cyclone Separator		LDO 25		TPM	50 Mg/Nm <sup>3</sup>
S -3	Kcal.Hr)	followed by Wet Scrubber	15.00	Kg/Hr	1.8	SO2	21.6 Kg/Day
S -4	Reactor 102, Tray Drier	Wet Scrubber	5.00	-	-	Acid Mist	35 Mg/Nm³
S -5	Reactor 201	Wet Scrubber	6.00	-	-	Acid Mist	35 Mg/Nm <sup>3</sup>
S -6	Reactor 202	Wet Scrubber	6.00	-	-	Acid Mist	35 Mg/Nm <sup>3</sup>
S -7	Standby to Process Reactors	Wet Scrubber	6.00	-	-	Acid Mist	35 Mg/Nm³
S -8	HCI Storage Tank	Wet Scrubber	6.00	-	-	Acid Mist	35 Mg/Nm <sup>3</sup>
S -9	DG Set- (500 KVA)	Acoustic Enclosure	6.00	HSD 200	1	TPM	50 Mg/Nm <sup>3</sup>
	DG 361 (300 KV/)	Acoustic Effetosure	0.00	Kg/Hr	_	SO2	32 Kg/Day
S -10	DG Set- (500 KVA)	Acoustic Enclosure	6.00	HSD 200	1	TPM	50 Mg/Nm <sup>3</sup>
			72	Kg/Hr		SO2	32 Kg/Day
6 11	Diesel Engine Fire	Charle	6.00	HSD 16	1	TPM	50 Mg/Nm <sup>3</sup>
S -11	pump	Stack	6.00	Kg/Hr	1	SO2	6.72 Kg/Day
S -12 Warehouse chemical dispensing		Wet Scrubber	4.00	-	-	Acid Mist	35 Mg/Nm³
S -13	DC-1 P-III- Micronisation	Dust Filter	1.00	-	-	Acid Mist	35 Mg/Nm³
S -14	DC-2 P-III- Micronisation	Dust Filter	1.00	-	-	Acid Mist	35 Mg/Nm³
S -15	DC-3 P-II- Sifter/Multimill	Dust Filter	3.00	-	-	Acid Mist	35 Mg/Nm³
S -16	DC-4 P-III- Micronisation	Dust Filter	1.00	-	-	Acid Mist	35 Mg/Nm³
S -17	DC-5-AHU Filter cleaning room	Dust Filter	1.00	-	-	Acid Mist	35 Mg/Nm³
S -18	DC-6-Behind warehouse (Micronisation)	Dust Filter	4.00	-	-	Acid Mist	35 Mg/Nm³
S -19	DC-7 P-III Multi Mill	Dust Filter	3.00	-	-	Acid Mist	35 Mg/Nm <sup>3</sup>
S -20	DC-8 P-III(Sifter Operation)	Dust Filter	3.00	-	-	Acid Mist	35 Mg/Nm³
S -21	Fume hood-QC lab	Dust Filter	3.00	-	-	Acid Mist	35 Mg/Nm <sup>3</sup>
S -22	Fume hood-PDL lab	Dust Filter	3.00	-	-	Acid Mist	35 Mg/Nm <sup>3</sup>

- 2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Parameters	Standards (unit)			
Total Particulate Matter	Not to exceed	50 mg/ Nm3		

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).
- 6. Solvent Management shall be carried out as follows:
  - a. Reactors shall be connected to Water / Chilled Water /Brine Condenser system.
  - b. Reactors and solvent handling pumps shall have mechanical seals to prevent the leakages.
  - c. The condensers shall be provided with adequate Heat transfer area (HTA) and residence time so as to achieve more than 97% overall recovery
  - d. Solvents shall be stored in a separate space specified with all safety measures.
  - e. Proper earthing shall be provided in all the equipment's, wherever solvent handling is done.
  - f. Entire plant shall be flame proof. The solvent storage tanks shall be provided with breather valve to prevent losses.
  - g. All the solvent storage tanks shall be connected with vent condensers with Water / chilled water / Brine circulation.
  - h. Fugitive emissions shall be controlled at 99.95% with effective chillers.
  - i. Solvent transfer shall be through pump.
  - j. Metering and control of quantities of active ingredients to minimize wastes.
  - k. Use of automatic filling to minimize spillage.
  - I. Use of close feed system into batch reactors.
  - m. Venting equipment through vapour recovery system.

#### **SCHEDULE-III**

#### **Details of Bank Guarantees:**

Sr. No.	Consent(C2E/C 20/C2R)	Amt of BG Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
1	C to R (existing to be extended)	Rs. 5 Lakh	15 days	Towards O & M of Pollution Control Systems & Compliance of Consent Conditions	30/09/2027	31/03/2028

<sup>\*\*</sup> The above Bank Guarantee(s) shall be submitted by the applicant in favour of Regional Officer at the respective Regional Office within 15 days of the date of issue of Consent.

# Existing BG obtained for above purpose if any may be extended for period of validity as above.

#### **BG** Forfeiture History

Srno.	Consent (C2E/C2O/C2R)	Amount of BG imposed	Submission Period	Purpose of BG	BU	BG
NA						

#### **BG Return details**

Srno.	Consent (C2E/C2O/C2R)	BG imposed	Purpose of BG	Amount of BG Returned			
	NA						

#### **SCHEDULE-IV**

#### **General Conditions:**

- 1. The waste generator shall.
  - a) take steps to minimize generation of plastic waste and segregate plastic waste at source in accordance with the Plastic Waste Management Rules, 2016 or as amended from time to time.
  - b) not litter the plastic waste and ensure segregated storage of waste at source and handover segregated waste to urban local body or gram panchayat or agencies appointed by them or registered waste pickers', registered recyclers or waste collection agencies;
- All institutional generators of plastic waste, shall segregate and store the waste generated by them in accordance with the Plastic Waste Management Rules, 2016 amendment from time to time and handover segregated wastes to authorized waste processing or disposal facilities or deposition centers either on its own or through the authorized waste collection agency.
- All waste generators shall pay such user fee or charge as may be specified in the byelaws of the local bodies for plastic waste management such as waste collection or operation of the facility thereof, etc.;
- 4. Every person responsible for organizing an event in open space, which involves service of food stuff in plastic or multilayered packaging shall segregate and manage the waste generated during such events in accordance with the Plastic Waste Management Rules, 2016 amendment from time to time.
- 5. Consumers or bulk consumers of electrical and electronic equipment listed in Schedule I shall ensure that e-waste generated by them is channelised through collection centre or dealer of authorised producer or dismantler or recycler or through the designated take back service provider of the producer to authorised dismantler or recycler
- 6. Bulk consumers of electrical and electronic equipment listed in Schedule I shall maintain records of e-waste generated by them in Form-2 and make such records available for scrutiny by the concerned State Pollution Control Board
- 7. Consumers or bulk consumers of electrical and electronic equipment listed in Schedule I shall ensure that such end-of-life electrical and electronic equipment are not admixed with e-waste containing radioactive material as covered under the provisions of the Atomic Energy Act, 1962 (33 of 1962) and rules made there under;
- 8. Bulk consumers of electrical and electronic equipment listed in Schedule I shall file annual returns in Form-3, to the concerned State Pollution Control Board on or before the 30th day of June following the financial year to which that return relates. In case of the bulk consumer with multiple offices in a State, one annual return combining information from all the offices shall be filed to the concerned State Pollution Control Board on or before the 30th day of June following the financial year to which that return relates.
- 9. Specific Conditions for storage, Handling and Disposal of Waste from Electrical & Electronic equipment (WEEE):
  - Collection of WEEE The applicant must provide appropriate and dedicated vehicles duly identified as per the norms for transportation of Hazardous Waste. The applicant shall obtain all the required permits for transportation of WEEE from competent authority. The applicant shall ensure the safe transport of the WEEE without any spillage during transportation.
    - **Storage for disassembled parts:** The applicant must provide appropriate storage for disassembled spare parts from WEEE. Some spare parts (e.g. motors and compressors) will contain oil and/or other fluids. Such part must be appropriately segregated and stored in containers that are secured such that oil and other fluids cannot escape from them. These containers must be stored on an area with an area with an impermeable surface and a sealed drainage system.

- 2. **Storage for other components and residues:**Other components and residues arising from the treatment of WEEE will need to be contained following their removal for disposal or recovery. Where they contain hazardous substances they should be stored on impermeable surface and in appropriate containers or bays with weatherproof covering. Containers should be clearly labelled to identify their contents and must be secured so that liquids, including rain water cannot enter them. Components should be segregated having regard to their eventual destinations and the compatibility of the component types. All batteries should be handled and stored having regard to the potential fire risk associated with team.
- 3. **Balances:** WEEE Guidelines also requires that sites for handling of WEEE have "balances to measure the weight of the segregated waste'. The objective is to ensure that a record of weights can be maintained of WEEE entering a facility and components and materials leaving each site (together with their destinations). The nature of the weighing equipment should be appropriate for the type and quantity of WEEE being processed.
- 4. Plastic, which cannot be recycled and is hazardous in nature, is recommended to be land filled in nearby CHWTSDF.
- 5. Ferrous and nonferrous metal recycling facilities fall under the purview of existing environmental regulations for air, water, noise, land and soil pollution and generation of hazardous waste and the same should be followed.
- 6. CFCS should be either reused or incinerated in common hazardous waste Incineration facilities at CHWTSDF.
- 7. Waste Oil should be either reused or incinerated in common hazardous waste incineration facilities.
- 8. PCB's containing capacitors shall be incinerated in common hazardous waste incineration facilities at CHWTSDF.
- 9. Mercury recovery and lead recycling facilities from batteries fall under the Hazardous & Other Wastes (M & TM) Rules, 2016.
- 10. Existing environmental regulations for air; water; noise, land and soil pollution and generation of hazardous waste and the same should be followed. In case Mercury or lead recovery is very low, they can be temporarily stored at e-waste recycling facility and later disposed in TSDF.
- 11. The industry shall maintain records of the e-waste purchased, processed in Form-2 and shall file annual returns of its activities of previous year in Form-3 as per Rules 11(9) & 13(3)(vii) of the E-Waste(M) Rules, 2016; on or before 30th day of June of every year.
- 10. The Energy source for lighting purpose shall preferably be LED based
- 11. The PP shall harvest rainwater from roof tops of the buildings and storm water drains to recharge the ground water and utilize the same for different industrial applications within the plant
- 12. Conditions for D.G. Set
  - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
  - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
  - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.

- d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- f) D.G. Set shall be operated only in case of power failure.
- g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h) The applicant shall comply with the notification of MoEFCC, India on Environment (Protection) second Amendment Rules vide GSR 371(E) dated 17.05.2002 and its amendments regarding noise limit for generator sets run with diesel.
- 13. The applicant shall maintain good housekeeping.
- 14. The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 15. The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 16. The Board reserves the right to review, amend, suspend, revoke this consent and the same shall be binding upon you.
- 17. The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).
- 18. The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 19. The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification No. B-29016/20/90/PCI-L dated. 18.11.2009 as amended.
- 20. This consent should not be construed as exemption from obtaining necessary NOC/ permission from any other Government authorities.
- 21. The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
- 22. You shall operate OCEMS installed for source emission round 'O' clock and transmit data online to CPCB and MPCB server. You shall also monitor effluent quality, stack emissions and ambient air quality monthly/quarterly. You shall conduct Dioxin Furan monitoring by third party NABL Accredited agency once in year and submit report to Sub Regional Officer.
- 23. You shall ensure collection, and segregation of BMW regularly to treat and dispose Off within 48 hrs from generation.
- 24. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 25. The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.

- 26. The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the Hazardous and Other Wastes (M & TM) Rules 2016, which can be recycled /processed /reused /recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc. should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 27. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 28. You shall not Rent, Lend, Sell, Transfer or Close Down the facility or otherwise transport the Bio Medical waste for any other purpose without obtaining prior written permission of the MPC Board.
- 29. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 30. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 31. The industry should not cause any nuisance in surrounding area.
- 32. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 33. You shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the facility premises.
- 34. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 35. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto
- 36. The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 37. The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
- 38. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions.

- 39. The firm shall submit to this office, the 30th day of September every year, the Environment Statement Report for the financial year ending 31st March in the prescribed FORM-V as per the provisions of Rule 14 of the Environment (Protection) (second Amendment) Rules, 1992.
- 40. You should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly. You shall conduct Dioxin Furan monitoring by third party NABL Accredited agency once in every year and submit report to Sub Regional Officer.
- 41. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).
- 42. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 43. You shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
- 44. You shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website (www.mpcb.gov.in).
- 45. You shall create the Environmental Cell by appointing an Environmental Engineer and Chemist for looking after day-to-day activities related to compliance of CCA.

46. You should comply with the Hazardous and Other Wastes (M & TM) Rules, 2016, Bio Medical Waste Management Rules, 2016 and submit the Annual Returns as per Rule 6(5) & 20(2) of Hazardous and Other Wastes (M & TM) Rules, 2016 for the preceding year in Form-IV by 30th June of every year This certificate is digitally & electronically signed.