

MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 0253 - 2365150
Fax: 0253 - 2365150
Website: <http://mpcb.gov.in>
Email: ronasik@mpcb.gov.in



Udyog Bhavan, First Floor,
Trimbak Road, Near ITI,
Satpur, Nashik - 422007

ORANGE/S.S.I (O70)
**No:- Format1.0/RO/UAN No.MPCB-
CONSENT_AMMENDMENT-0000019465/CO/260300018
1**

Date: 18/03/2026

To,
M/s. SHREE R. R.
Plot No.1 TO 7, Gat No.58/1+58/A,At-Bedkipada,
Tal.Navapur, ,Dist. Nandurbar.



Sub: Grant of amedment in consent to 1st operate for change in name.

Ref: Earlier Board had granted the consent vide no. Format1.0/RO/UAN No.0000207488/CO/2407002286 Date: 24/07/2024,

Your application No.MPCB-CONSENT_AMMENDMENT-0000019465 Dated 01.02.2026

For: grant of Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 6 and Rule 18(7) of the Hazardous & Other Wastes (Management & Transboundary Movement) Rules 2016 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- The consent to operate is granted for a period up to 30/04/2027**
- The capital investment of the project is Rs.0.4 Crs. (As per C.A Certificate submitted by industry 0.6038)**
- Consent is valid for the manufacture of:**

Sr No	Product	Maximum Quantity	UOM
Products			
1	PYROLYSIS OIL	2560	MT/A
2	CARBON BLACK POWDER	2160	MT/A
By Products			
3	RECOVERED STEEL	700	MT/A

- Conditions under Water (P&CP), 1974 Act for discharge of effluent:**

Sr No	Description	Permitted (in CMD)	Standards to	Disposal Path
1.	Trade effluent	0.7	As per Schedule -I	On land for gardening
2.	Domestic effluent	0.50	As per Schedule - I	Soaked in soak pit

5. **Conditions under Air (P& CP) Act, 1981 for air emissions:**

<i>Sr No.</i>	<i>Stack No.</i>	<i>Description of stack / source</i>	<i>Number of Stack</i>	<i>Standards to be achieved</i>
1	1	REACTORS (5 Nos)	1	As per Schedule -II

6. **Non-Hazardous Wastes:**

<i>Sr No</i>	<i>Type of Waste</i>	<i>Quantity</i>	<i>UoM</i>	<i>Treatment</i>	<i>Disposal</i>
1	Waste Tyre Scrap	234	MT/A	NA	Sale to authorized party

7. **Conditions under Hazardous & Other Wastes (M & T M) Rules 2016 for Collection, Segregation, Storage, Transportation, Treatment and Disposal of hazardous waste:**

<i>Sr No</i>	<i>Category No./ Type</i>	<i>Quantity</i>	<i>UoM</i>	<i>Treatment</i>	<i>Disposal</i>
1		0	--NA--	NA	NA

8. The Board reserves the right to review, amend, suspend, revoke this consent and the same shall be binding on the industry.
9. This consent should not be construed as exemption from obtaining necessary NOC/ permission from any other Government authorities.
10. The applicant shall make an application for renewal of consent 60 days prior to date of expiry of the consent.
11. The use of Banned Plastic and Thermocol Products as per Maharashtra Plastic and Thermocol Products Notification, 2018 is not permitted. The project proponent shall comply with Maharashtra Plastic & Themocol Products Notification,2018
12. The industry shall obtain necessary permission from the Directorate of Industrial Safety and Health(DISH).
13. The applicant shall obtain NOC from CGWA for ground water extraction.
14. The applicant shall strictly follow the Guidelines prepared by MPCB for Tyre Retreating and Recycling.
15. The applicant shall comply with SOP (Standard Operating Procedure) for tyre pyrolysis issued by CPCB vide dtd. 16/01/2024.



16. Specific Conditions: (i) Industry shall make necessary provisions for storage of carbon dioxide gas which is used for degassing of the reactor to vent out off gases through condenser - water - burning chamber where these gases are burnt into flame. The degassing of reactor by carbon dioxide shall be done so as to ensure safe closure of the batch process. (ii) The flue gases from burning chamber, if any specifically during startup and burning of excess off gases from reactor, shall be vent out through chimney having adequate height 11 mtrs. Or as per provisions of emission regulation Part-IV issued by CPCB whichever is higher. (iii) Industry shall use clean fuel such a LPG/PNG during startup of the reactor. (iv) Industry shall ensure that there are no leakages from reactor, piping so as to minimize fugitive emissions. The records of preventive maintenance schedule of burner, reactor vessel, pyrolysis chamber and allied piping shall be maintained and made available for inspection during official visits. (v) The pyrolysis oil condensed from the vessel shall be collected in storage tanks located in earmarked areas. The pipelines shall be equipped with floating valve so as to avoid spillage due to overflow. (vi) There shall not be spillage of pyrolysis oil in and around the factory premises. (vii) Pyrolysis oil tanks shall be provided with arrangement of dyke wall and necessary safety arrangements. (viii) The vent of pyrolysis oil tanks shall be Specific Conditions: (i) Industry shall make necessary provisions for storage of carbon dioxide gas which is used for degassing of the reactor to vent out off gases through condenser - water - burning chamber where these gases are burnt into flame. The degassing of reactor by carbon dioxide shall be done so as to ensure safe closure of the batch process. (ii) The flue gases from burning chamber, if any specifically during startup and burning of excess off gases from reactor, shall be vent out through chimney having adequate height 11 mtrs. Or as per provisions of emission regulation Part-IV issued by CPCB whichever is higher. (iii) Industry shall use clean fuel such a LPG/PNG during startup of the reactor. (iv) Industry shall ensure that there are no leakages from reactor, piping so as to minimize fugitive emissions. The records of preventive maintenance schedule of burner, reactor vessel, pyrolysis chamber and allied piping shall be maintained and made available for inspection during official visits. (v) The pyrolysis oil condensed from the vessel shall be collected in storage tanks located in earmarked areas. The pipelines shall be equipped with floating valve so as to avoid spillage due to overflow. (vi) There shall not be spillage of pyrolysis oil in and around the factory premises. (vii) Pyrolysis oil tanks shall be provided with arrangement of dyke wall and necessary safety arrangements. (viii) The vent of pyrolysis oil tanks shall be Specific Conditions: (i) Industry shall make necessary provisions for storage of carbon dioxide gas which is used for degassing of the reactor to vent out off gases through condenser - water - burning chamber where these gases are burnt into flame. The degassing of reactor by carbon dioxide shall be done so as to ensure safe closure of the batch process. (ii) The flue gases from burning chamber, if any specifically during startup and burning of excess off gases from reactor, shall be vent out through chimney having adequate height 11 mtrs. Or as per provisions of emission regulation Part-IV issued by CPCB whichever is higher. (iii) Industry shall use clean fuel such a LPG/PNG during startup of the reactor. (iv) Industry shall ensure that there are no leakages from reactor, piping so as to minimize fugitive emissions. The records of preventive maintenance schedule of burner, reactor vessel, pyrolysis chamber and allied piping shall be maintained and made available for inspection during official visits. (v) The pyrolysis oil condensed from the vessel shall be collected in storage tanks located in earmarked areas. The pipelines shall be equipped with floating valve so as to avoid spillage due to overflow. (vi) There shall not be spillage of pyrolysis oil in and around the factory premises. (vii) Pyrolysis oil tanks shall be provided with arrangement of dyke wall and necessary safety arrangements. (viii) The vent of pyrolysis oil tanks shall be equipped with adequate capacity carbon filters so as to minimize emissions of off gases to avoid smell nuisance. The carbon filter's media (fine carbon particle size) shall be replaced periodically to ensure effective adsorption of gases. (ix) Industry shall maintain logbook which will specify plant operation time, raw material dead stock, product logistics along with their specifications, logistics of carbon dioxide, records of preventive maintenance etc. The records shall be made available to officials during inspections. (x) Industry shall make earmarked storage area for raw materials which shall be covered with shed. The storage area shall have cement concrete flooring with plinth height of 0.5 Mtrs. above the ground. (xi) Industry shall maintain minimum distance of 10 Mtrs. between plant area, raw material storage area, carbon black storage area and pyrolysis oil storage area. (xii) Industry shall keep 10 Mtrs. free passage area within work environment so as to get direct access to plant / raw material storage / carbon black storage area and pyrolysis oil storage area in case of emergencies. (xiii) Adequate fire fighting system shall be provided as per prevailing norms laid down by competent authority. (xiv) The industry shall comply provisions of "The Manufacture, Storage & Import of Hazardous Chemicals Rules, 1989". (xv) The rules and regulations notified by Ministry of Law and Justice, Govt. of India regarding Public Liabilities Insurance Act, 1991 shall be followed. (xvi) Industry shall prepare on site and off site disasters management plan which shall be approved by competent authorities. (xvii) Industry shall not carry out further processing of pyrolysis oil. (xviii) The byproducts like steel wire shall be collected properly and stored in closed shed. 6. Other Conditions: (i) Suitable sensor will be installed to ensure that all gases from the reactor have been evacuated before opening of the reactor for transfer of carbon black / steel wire. (ii) That the produced carbon black will be conveyed through hydraulic / screw conveyor in closed conditions. The carbon black generated from the manufacturing process can also be conveyed / collected / handled by using any other suitable technology, provided the state Board considers the technology to be appropriate. (iii) It shall be ensured that all the materials have been completely removed from the reactor for which a glass inspection window with provision of lights (illumination) shall be provided at the outer enclosures of the reactor. The end of the conveyor will be attached to a bagging plant where all the carbon black will be bagged in HDPE bags and the bags will be properly sealed. (iv) The bagging plant will be equipped with requisite air pollution control arrangements such as dust extraction system, bag filter to arrest all the carbon particles which may get air borne during bagging process and a vent of minimum height of 11m from the ground level. (v) Industry shall carry out ambient air quality monitoring at three locations simultaneously within their premises in consultation with the Regional Officer to monitor RSPM, carbon monoxide and methane / ethane gases at least once in three months through a recognized laboratory or by the industry. It will be ensured that monitoring shall be carried out only during the period when the plant is in operation.

17. The industry shall comply with orders passed or to be passed by any Judicial authority/Hon'ble National Green Tribunal regarding Tyre Pyrolysis activity.
18. i. Industry shall provide fumes extraction system followed by dust collection system to carbon black handling section (s). ii. Industry shall provide dust collector followed by wet scrubber to Pyrolysis Kilns/Reactors. iii. There shall not be any secondary (fugitive) emissions. iv. Industry shall install sensors for gases like CO along with alarms set at suitable threshold limit. The necessary piping arrangements for gases along with sensors shall be done in the work environment so as ensure safe operational practices.
19. The industry shall comply with of standard operating procedures (SOPs) with regard to waste pneumatic tyre and recovery of TPO from tyre scrap published by Ministry of Environment and Forest and Climate Change, HSM Division, Govt. of India vide office memorandum dtd. 24.11.2015 before commencement of production activity
20. i. Suitable sensor will be installed to ensure that all gases from the reactor have been evacuated before opening of the reactor for transfer of carbon black / steel wire . ii. That the produced carbon black will be conveyed through hydraulic / screw conveyor in closed conditions. The carbon black generated from the mfg. process can also be conveyed / collected / handled by using any other suitable technology provided by the state board considering the technology to be appropriate. iii. It shall be ensured that the all the materials have been completely removed from the reactor for which a glass inspection window with provision of light (illumination) shall be provided at the outer enclosures of the reactor.The end of the conveyor will be attached to the bagging plant where all the carbon black will be bagged in HDPE bags and the bags will be properly sealed. iv. The bagging plant will be equipped with requisite air pollution control arrangements such as dust extraction system , back filter to arrest all the carbon particles which may get air born during bagging process and a vent of minimum height of 11m from the ground level. v. Industry shall carry out ambient air quality monitoring at three locations simultaneously within their premises in consultations with the Regional Officer to monitor RSPM, carbon monoxide and methane / ethane gases at least once in three months through recognized laboratory or by the industry . It will be ensured that monitoring shall be carried out during the period when the plant is in operation
21. This consent has Overriding effect on earlier consent granted vide letter no. Format1.0/RO/UAN No.0000207488/CO/2407002286 Date: 24/07/2024.
22. The applicant shall make an application for renewal of consent 120 days prior to date of expiry of the consent. (Operate/Renewal)

This consent is issued on the basis of information/documents submitted by the Applicant/Project Proponent, if it has been observed that the information submitted by the Applicant/Project Proponent is false, misleading or fraudulent, the Board reserves its right to revoke the consent & further legal action will be initiated against the Applicant/Project Proponent.

Received Consent fee of -

Sr.No	Amount(Rs.)	Transaction/DR.No.	Date	Transaction Type
1	1500.00	TXN2404004707	26/04/2024	Online Payment
2	13500.00	TXN2407004120	22/07/2024	Online Payment

Copy to:

1. Regional Officer, MPCB, Nashik and Sub-Regional Officer, MPCB, Dhule
- They are directed to ensure the compliance of the consent conditions.
2. Chief Accounts Officer, MPCB,Sion, Mumbai

SCHEDULE-I

Terms & conditions for compliance of Water Pollution Control:

1. A] As per your application, you have provided Effluent Treatment Plant (ETP) of designed capacity of 1.00 CMD consisting of Primary (Collection tank) for the treatment of 0.7 CMD of trade effluent.
- B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent:

Sr.No	Parameters	Limiting concentration not to exceed in mg/l, except for pH
(1)	pH	6.0 -8.5
(2)	BOD (3 days 27°C)	30
(3)	COD	250
(4)	Oil & Grease	10
(5)	TDS	2100
(6)	Suspended Solids	100
(7)	Sulphate	1000
(8)	Chloride	600

- C] separate energy meter for pollution control system shall be provided.
 - D] The treated effluent shall be recycled for secondary purposes to the maximum extent and remaining shall be discharged on land for gardening within premise after confirming above standards. In no case, effluent shall find its way for gardening / outside factory premises.
2. A] As per your application, you have provided Septic Tank followed by Soak pit for the treatment of 0.50 CMD of sewage.
 - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards.

Sr.No	Parameters	Standards (mg/l)	
1	Suspended Solids	Not to exceed	100
2	BOD 3 days 27°C	Not to exceed	100

- C] The treated sewage shall be recycled for secondary purposes to the maximum extent and remaining shall be discharged on land for gardening within premise after confirming above standards. In no case, sewage shall find its way for gardening / outside factory premises.
3. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification there of & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto.

4. The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
5. The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Act, 1974 and as amended, by installing water meters and other provisions as contained in the said act:

Sr. No.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	1.20
2.	Domestic purpose	0.70
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	0.00
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	0.00
5.	Gardening	0

6. The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance/ CREP guidelines.

SCHEDULE-II

Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC) system and erected following stack (s) to observe the following fuel pattern:

Stack No.	Source	APC System provided/proposed	Stack Height(in mtr)	Type of Fuel	Sulphur Content(in %)	Pollutant	Standard
1	REACTORS (5 Nos)	Scrubber	24.00	Wood/pyrogas 150 Kg/Day	-	TPM	-

2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.
3. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.
4. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

SCHEDULE-III

Details of Bank Guarantees:

Sr. No.	Consent(C2E/C2O/C2R)	Amt of BG Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
1	C2O	1.0 Lakh	within 15 days	TOWARDS OPERATION AND MAINTENANCE OF POLLUTION CONTROL SYSTEM	CONTINUOUS	31.08.2027
2	C2O	1.0 Lakh	within 15 days	TOWARDS PROVISION AND OPEARATION OF SUITABLE SENSORS, FOR GAS, TEMP., AND PRESSURE INSTALLED INSIDE THE REACTOR TO REGULATE SAFE OPERATION OF THE REACTOR AND PROPER COLLECTION SYSTEM FOR TOXIC GASES	CONTINUOUS	31.08.2027
3	C2O		within 15 days	TOWARDS PROVISION AND OPERATION OF HYDRAULIC/SCREW CONVEYOR FOR CONVEYANCE OF THE PRODUCED CARBON BLACK IN CLOSED CONDITIONS	CONTINUOUS	31.08.2027

** The above Bank Guarantee(s) shall be submitted by the applicant in favour of Regional Officer at the respective Regional Office within 15 days of the date of issue of Consent.

Existing BG obtained for above purpose if any may be extended for period of validity as above.

BG Forfeiture History

Srno.	Consent (C2E/C2O/C2R)	Amount of BG imposed	Submission Period	Purpose of BG	Amount of BG Forfeiture	Reason of BG Forfeiture
NA						

BG Return details

Srno.	Consent (C2E/C2O/C2R)	BG imposed	Purpose of BG	Amount of BG Returned
NA				

SCHEDULE-IV
General Conditions:

1. The Energy source for lighting purpose shall preferably be LED based
2. The PP shall harvest rainwater from roof tops of the buildings and storm water drains to recharge the ground water and utilize the same for different industrial applications within the plant
3. Conditions for D.G. Set
 - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
 - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
 - f) D.G. Set shall be operated only in case of power failure.
 - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
 - h) The applicant shall comply with the notification of MoEFCC, India on Environment (Protection) second Amendment Rules vide GSR 371(E) dated 17.05.2002 and its amendments regarding noise limit for generator sets run with diesel.
4. The applicant shall maintain good housekeeping.
5. The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
6. The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
7. The Board reserves the right to review, amend, suspend, revoke this consent and the same shall be binding upon you.
8. The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can be downloaded from MPCB official site).
9. The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
10. The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification No. B-29016/20/90/PCI-L dated. 18.11.2009 as amended.
11. This consent should not be construed as exemption from obtaining necessary NOC/ permission from any other Government authorities.

12. The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
13. You shall operate OCEMS installed for source emission round 'O' clock and transmit data online to CPCB and MPCB server. You shall also monitor effluent quality, stack emissions and ambient air quality monthly/quarterly. You shall conduct Dioxin Furan monitoring by third party NABL Accredited agency once in year and submit report to Sub Regional Officer.
14. You shall ensure collection, and segregation of BMW regularly to treat and dispose Off within 48 hrs from generation.
15. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
16. The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
17. The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the Hazardous and Other Wastes (M & TM) Rules 2016, which can be recycled /processed /reused /recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc. should go for that purpose, in order to reduce load on incineration and landfill site/environment.
18. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
19. You shall not Rent, Lend, Sell, Transfer or Close Down the facility or otherwise transport the Bio Medical waste for any other purpose without obtaining prior written permission of the MPC Board.
20. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
21. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
22. The industry should not cause any nuisance in surrounding area.
23. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
24. You shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the facility premises.

25. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
26. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto
27. The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
28. The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
29. The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions.
30. The firm shall submit to this office, the 30th day of September every year, the Environment Statement Report for the financial year ending 31st March in the prescribed FORM-V as per the provisions of Rule 14 of the Environment (Protection) (second Amendment) Rules, 1992.
31. You should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly. You shall conduct Dioxin Furan monitoring by third party NABL Accredited agency once in every year and submit report to Sub Regional Officer.
32. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).
33. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
34. You shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
35. You shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website (www.mpcb.gov.in).
36. You shall create the Environmental Cell by appointing an Environmental Engineer and Chemist for looking after day-to-day activities related to compliance of CCA.
37. You should comply with the Hazardous and Other Wastes (M & TM) Rules, 2016 , Bio Medical Waste Management Rules,2016 and submit the Annual Returns as per Rule 6(5) & 20(2) of Hazardous and Other Wastes (M & TM) Rules, 2016 for the preceding year in Form-IV by 30th June of every year

This certificate is digitally & electronically signed.

